BATHING ROOMS

- 31.7.5 Grab bars: Two grab bars shall be provided as shown in Fig. 31c and 31d.
 - a. They shall be placed horizontally between 33 and 36 inches (33" to 36" = 838mm to 914mm) above the floor line. In a 36 by 36 inch (36" by 36" = 914mm by 914mm) stall, two 30 inch (30" = 762mm) grab bars shall be provided, one on the back wall and one on the wall opposite the seat. In a 30 inch by 60 inch (30" by 60" = 762mm by 1524mm), two grab bars, one 42 inches (42"= 1067mm) long and one 24 inches (24" = 608mm) long shall be installed on the long wall and the short wall opposite the seat. In the alternative, a continuous L-shaped grab bar in the shower is acceptable.
 - b. The structural strength of grab bars and their attachments shall comply with the definition of structural strength in 521 CMR 5, DEFINITIONS.
 - c. Grab bars shall be $1\frac{1}{4}$ inches to $1\frac{1}{2}$ inches ($1\frac{1}{4}$ " to $1\frac{1}{2}$ " = 32mm to 38mm) in outside diameter, and have a $1\frac{1}{2}$ inch ($1\frac{1}{2}$ " = 38mm) clearance between the bar and the wall. See Fig. 25a.
 - d. Grab bars shall also be non-rusting and acid-etched or roughened.
- 31.7.6 Soap trays shall not incorporate hand hold features unless they can support 250 pounds for five minutes.
- 31.7.7 Spray Shower Unit. A shower spray unit attached to a flexible metal hose at least 60 inches (60" = 1524mm) long and adjustable from 42 inches to 72 inches (42" to 72" = 1067mm to 1829mm) that can be used both as a fixed shower head and as a hand-held shower shall be provided.

Exception: In unmonitored facilities where vandalism is a consideration, a fixed shower head mounted at 48 inches (48" = 1219mm) above the shower floor may be used in lieu of a hand-held shower head.

- 31.7.8 Curbs: If provided, curbs in shower stalls 36 inches by 36 inches (36" by 36" = 914mm by 914mm) shall be no higher than $\frac{1}{2}$ inch ($\frac{1}{2}$ " = 13 mm). Shower stalls that are 30 inches by 60 inches (30" by 60" = 762mm by 1524mm) minimum shall not have curbs.
- 31.7.9 Shower Enclosures: If provided, enclosures for shower stalls shall not obstruct controls or obstruct transfer from wheelchairs onto shower seats.
- 31.8 GANG SHOWERS Shall also comply with 521 CMR 31 except for the provisions contained in 521 CMR 31.7.1.
- 31.9 BATHTUBS

 Accessible bathtubs shall comply with the following:
- 31.9.1 Clear floor space: Clear floor space in front of bathtubs shall be as shown in Fig. 31e and 31f.

